

Square Type Glass Spigot - 10-21.52mm - With Cover (Model: KCVSP003)









- Suitable for 10mm to 21.52mm thick glass.
- Manufactured using Duplex 2205 grade stainless steel for use in the most harsh outdoor environments.
- Glass alignment can be easily achieved by shimming the base of the spigot.
- No glass drilling is required.
- 2 Spigots per metre.
- Replacement Cover also available (KCVSP004).

Attributes:

Product Code: KCVSP003 **Unit Of Sale:** EACH







Type of Occupancy for Part of the Building	Examples of Specific Use	Horizontal Uniformly Distributed Line Load (kNim)	Budget Square Spigots 19 mm Toughened	Budget Round Spigots 1900 mm Panel				
				12 mm Toughened	15 mm Toughened	17.5 mm Laminated	19 mm Toughened	21.5 mm Laminated
Demestic and residential activities	(i) all areas within or serving exclusively one single family dwelling including stairs, landings, etc. but excluding external balconies and edges of roofs	0.36	-		,		,	
	(ii) other residential, i.e. houses of multiple cocupancy and balosnies, including Juliete balconies and edges of roofs in single family dwellings	0.74	-	х	,			-
Offices and work areas not included alsowhere, including storage areas	(ii) light access stairs and gangways not more than 600 mm wide	0.22	-	-	-	-	-	-
	(iv) light pedestrian traffic routes in industrial and storage buildings except designated escape routes	0.36	-	-	-	-	-	-
	(v) areas not susceptible to overcrowding in office and institutional buildings, also industrial and storage buildings except as given above	0.74	-	х				
Areas where people might congregate	(vi) areas having fixed seating within \$30 mm of the barrier, balustrade or parapet	1.50	-	х	×	×	×	×
Areas with tobles or fixed seating	(vi) restaurants and bars	1.50	-	×	х	ж	×	×

Type of Occupancy for Part of the Building	Examples of Specific Use	Horizontal Uniformly Distributed Line Load ONVII)	Budget Square Spigets 19 mm Toughened	Budget Round Spigots 1000 mm Panel					
				12 mm Toughened	15 mm Toughered	17.5 mm Laminated	19 mm Toughered	21.5 mm Laminates	
Areas without obstacles for moving people and not susceptible to everorewing	(vii) stairs, landings corridors ramps	0.74	· ·	-	~	-	V	- /	
	(ix) external balconies including Juliette balconies and edges of node; tookways and povements within building cartilage adjacent to basement'sunken areas	0.74		×	~		~		
Areas susceptible is eventrewthing	(x) footways or pevements less than 3 m wide adjacent to sunken areas	1.50	-	×	×	ж	×	х	
	(xit threatives, cinemas, discotheques, bors, auditorie, shopping mells, assembly areas, studies, foothways or povements greater than 3 m wide adjacent to sunken areas	3.00	×	х	х	×	х	х	
	(xii) grandstends and stadia	(Note 1)							
Retail areas	(xii) all retail areas including public areas of banks/building societies or betting shops	1.50	х	×	х	×	х	×	
Vehicular	(ski) pedestrian areas in car parks, including stairs, lendings, ramps, edges of internal floors, footways, edges of noofs	(Note 2)	×	×	х	х	х	×	
	(xx) horizontal loads imposed by vehicles	(Note 2)	×	×	×	×	×	×	